



Unit 626 Kilshane Avenue, North West Business Park, Ballycoolin, Dublin 15, Ireland  
 Telephone: +353 1 8612 632, Fax: +353 1 8612 647, email: sales@driveriteltd.com

**FIAT DUCATO, CITROEN C25,**  
**PEUGEOT J5, TALBOT EXPRESS.**  
**EURO CHASSIS 280/290.**  
**LINK LSV**  
**W21-760-3149**

**INSTALLATION INSTRUCTIONS**

All work should be carried out in a properly equipped workshop with due regard to Health and Safety Regulations. No further reference to Health and Safety Regulations will be made, but they must be considered at all times.

The kit should be opened and the contents checked against the parts list provided.

Identify the various components and familiarise yourself with them using drawings and information provided.

**WARNING**

*Do not inflate this assembly when it is unrestricted. When installed, a minimum of 10 psi should be maintained in the air bellows at all times to avoid damage. Do not inflate beyond 100 psi.*

**IMPORTANT**

*This kit is not designed to increase the GVW of your vehicle. For your safety and to prevent possible damage to your vehicle, do not exceed the maximum load recommended by the vehicle manufacturer.*

	<p><b>LSV - Model type 230</b></p> <p>After the assembly of the air bellows the LSV must be pre-loaded to increase the automatic Load Sensing. The original bracket must be exchanged by a longer bracket, which is included in the kit. The position of this bracket must be made in such a way that the distance between the upper and the lower points as shown amounts to 155 mm. See Photograph.</p>
--	---